



THE AGRO POWER TECHNOLOGIES PRESENTS COMPREHENSIVE RANGE OF NO. 1 WORLDWIDE STIHL® CHAIN SAWS:



THE LEGENDARY HIGH QUALITY STIHL® PRODUCTS DOESN'T NEED ANY LENGTHY EXPLANATION; THE PRODUCTS TALK THEMSELVES BY THEIR SHEER OUTLOOK AND PERFORMANCE

COMPACT SAWS:

STIHL COMPACT SAWS ARE SUITABLE FOR MANY TASKS AROUND THE HOME YARD AND GARDENS, SUCH AS KEEPING TREES IN SHAPE, THINNING WORK OR CUTTING FIRE WOOD. THEY FEATURE TECHNOLOGY AND SAFETY EQUIPMENT DERIVED FROM THE PROFESSIONAL SAWS ARE EASY TO HANDLE AND ERGONOMICALLY DESIGNED TO REDUCE OPERATOR EFFORT.



SPECIFICATIONS	MS 170	MS 180	MS 230	MS 250
ENGINE	2 STROKE AIR COOLED	2 STROKE AIR COOLED	2 STROKE AIR COOLED	2 STROKE AIR COOLED
DISPLACEMENT	30.1 CC	31.8 CC	45.4 CC	45.4 CC
POWER OUTPUT	1.3 KW/1.8 BHP	1.5 KW/2.0 BHP	2.0 KW/2.7 BHP	2.3 KW/3.1 BHP
MAX.ENGINE SPEED	13500 RPM	14000 RPM	14000 RPM	14000 RPM
WEIGHT/POWER RATIO	3.0 KG/KW	2.6 KG/KW	2.4 KG/KW	2.0 KG/KW
WEIGHT W/O BAR & CHAIN	3.9 KG	4.3 KG	4.6 KG	4.6 KG
STD.GUIDE BAR SIZE	14" (35 CM) /16" (40 CM)	14" (35 CM) /16" (40 CM)	16" / 40 CM	16" / 40 CM
CHAIN PITCH X GAUGE	3/8" X 1.3 MM	3/8" X 1.3 MM	3/8" X 1.3 MM	3/8" X 1.3 MM
FUEL TANK CAPACITY	0.25 L	0.25 L	0.47 L	0.47 L
CHAIN OIL CAPACITY	0.15 L	0.15 L	0.20 L	0.20 L

ALL ROUND SAWS

ALLROUND SAWS HELP RELIEVE CUTTING EFFORT BECAUSE THEY OFFER VERY GOOD PERFORMANCE AND CONVINCING CONVENIENCE FEATURES: OPTIMUM CENTER OF GRAVITY FOR GOOD BALANCE, EASE OF OPERATION, INSTANT ACCELERATION AND HIGH TORQUE.

TYPICAL AREA OF APPLICATION ARE: AROUND THE HOME, YARD AND GARDEN, HARVESTING SMALL SIZED TIMBER AND CUTTING FIREWOOD.



SPECIFICATIONS	MS 290	MS 390
ENGINE	2 STROKE AIR COOLED	2 STROKE AIR COOLED
DISPLACEMENT	56.5 CC	64.1 CC
POWER OUTPUT	3.0 KW/4.1 BHP	3.4 KW/4.6 BHP
MAX.ENGINE SPEED	13000 RPM	13000 RPM
WEIGHT/POWER RATIO	2.0 KG/KW	1.7 KG/KW
WEIGHT W/O BAR & CHAIN	5.9 KG	5.9 KG
STD.GUIDE BAR SIZE	16" / 40 CM	18" / 45 CM
CHAIN PITCH X GAUGE	3/8" X 1.6 MM	3/8" X 1.6 MM
FUEL TANK CAPACITY	0.56 L	0.56 L
CHAIN OIL CAPACITY	0.33 L	0.33 L

ARBORIST SAWS

FOR PROFESSIONAL ARBORISTS INTERNATIONALLY. THEY ARE DESIGNED FOR WORK IN THE TREES, ARE EXCEPTIONALLY HANDY AND PROVIDE EXACT CONTROL; LOW KICKBACK STARTING, THANKS TO MICROPROCESSOR BASED IGNITION AND OPTIMAL ERGONOMICS. THE HIGH CHAIN SPEED ENSURES A PARTICULARLY CLEAN CUT TO REDUCE THE RISK OF TEARING BARK.



SPECIFICATIONS	MS 192 T	MS 200 T
ENGINE	2 STROKE AIR COOLED	2 STROKE AIR COOLED
DISPLACEMENT	30.1 CC	35.2 CC
POWER OUTPUT	1.3 KW/1.8 BHP	1.7 KW/2.3 HP
MAX.ENGINE SPEED	13500 RPM	14000 RPM
WEIGHT/POWER RATIO	3.0 KG/KW	2.1 KG/KW
WEIGHT W/O BAR & CHAIN	3.0 KG	3.5 KG
STD.GUIDE BAR SIZE	14" / 35 CM	14" (35 CM) / 16" (40 CM)
CHAIN PITCH X GAUGE	3/8" X 1.3 MM	3/8" X 1.3 MM
FUEL TANK CAPACITY	0.27 L	0.37 L
CHAIN OIL CAPACITY	0.22 L	0.24 L

PROFESSIONAL CHAIN SAW SERIES

A. MID RANGE PROFESSIONAL SAWS

CONVENIENT TECHNOLOGY WITH NOT A GRAM TOO MUCH WEIGHT, THESE CHAIN SAWS ARE INDISPENSABLE IN THE WOODS AND LANDSCAPE MAINTENANCE; DESIGNED FOR CONTINUOUS WORK WITH FULL FLEDGED CRANKCASE, HEAVY DUTY CRANKSHAFT & BEARINGS AND PROFESSIONAL ANTI-VIBRATION SYSTEM. AREA OF APPLICATION RANGE FROM THINNING WORK TO HARVESTING SMALL SIZED TIMBER AND LOGGING IN MEDIUM STANDS



SPECIFICATIONS	MS 260	MS 361	MS 381
ENGINE	2 STROKE AIR COOLED	2 STROKE AIR COOLED	2 stroke Air cooled
DISPLACEMENT	50.2 CC	59 CC	72.2 CC
POWER OUTPUT	2.6 KW/3.5 BHP	3.4 KW/4.6 BHP	3.9 KW/5.3 BHP
MAX.ENGINE SPEED	14000 RPM	13000 RPM	13000 RPM
WEIGHT/POWER RATIO	1.8 KG/KW	1.7 KG/KW	1.7 KG/KW
WEIGHT W/O BAR & CHAIN	4.7 KG	5.6 KG	6.6 KG
STD.GUIDE BAR SIZE	16" (40 CM)	18" (45 cm)	18" (45 CM)
CHAIN PITCH X GAUGE	.325" X .063"	3/8" X .063"	3/8" X .063"
FUEL TANK CAPACITY	0.460 L	0.685 L	0.680 L
CHAIN OIL CAPACITY	0.290 L	0.325 L	0.360 L

B. HEAVY DUTY PROFESSIONAL SAWS

THESE CAN BE USED FOR PROFESSIONAL APPLICATION, CONTINUOUSLY FOR EIGHT HOURS A DAY; APPLICION VARIES FROM FELLING BIG TREES TO CROSS CUTTING THE FALLEN TREES. HIGH POWER OUTPUT COMBINED WITH LOW WEIGHT ENABLES THE OPERATORS TO WORK EFFICIENTLY AND GET MAXIMUM OUPUT



SPECIFICATIONS	MS 460	MS 660	MS 880
ENGINE	2 STROKE AIR COOLED	2 STROKE AIR COOLED	2 STROKE AIR COOLED
DISPLACEMENT	76.5 CC	91.6 CC	121.6 CC
POWER OUTPUT	4.4 KW/6 BHP	5.2 KW/7.1 BHP	6.4 KW/8.7 BHP
MAX.ENGINE SPEED	14000 RPM	13500 RPM	13000 RPM
WEIGHT/POWER RATIO	1.5 KG/KW	1.4 KG/KW	1.55 KG/KW
WEIGHT W/O BAR & CHAIN	6.5 KG	7.3 KG	9.9 KG
STD.GUIDE BAR SIZE	18" (45 CM)	20" (50 CM)	24" (63 CM) / 30" (75 CM)
CHAIN PITCH X GAUGE	3/8" X .063"	3/8" X .063"	0.404" X .063"
FUEL TANK CAPACITY	0.8 L	0.825 L	1.3 L
CHAIN OIL CAPACITY	0.325 L	0.360 L	0.7 L

Available at:

THE AGRO POWER TECHNOLOGIES, 53/1, KOTTIGEPALYA, MAGADI ROAD, BANGALORE 560091, TEL: 9379844447, e mail: info@agropower.in, Website: www.agropower.in