

| Model | Displacement cm ³ | Power output kW/bhp | Weight kg ¹⁾ | Cutting tool | Elasto- Start | Anti-vibration system | Decom- pression valve | Handle adjustment without tools | Double handle |
|--------------|---------------------------------|---------------------------|----------------------------|--------------------------------|------------------|--------------------------|-----------------------------|---------------------------------------|------------------|
| FS 310 | 36.3 | 1.4/1.9 | 7.2 | Brush knife | - | ■ | - | ■ | ■ |
| FS 350 | 40.2 | 1.6/2.2 | 7.3 | Brush knife | ■ | ■ | ■ | ■ | ■ |
| FS 400 | 40.2 | 1.9/2.6 | 8.0 | Brush knife | ■ | ■ | ■ | ■ | ■ |
| FS 400-K | 40.2 | 1.9/2.6 | 8.1 | Circular saw | ■ | ■ | ■ | ■ | ■ |
| FS 450 | 44.3 | 2.1/2.9 | 8.0 | Brush knife | ■ | ■ | ■ | ■ | ■ |
| FS 450-K | 44.3 | 2.1/2.9 | 8.1 | Circular saw | ■ | ■ | ■ | ■ | ■ |
| FS 480 | 48.7 | 2.2/3.0 | 8.0 | Brush knife | ■ | ■ | ■ | ■ | ■ |
| FS 480-K | 48.7 | 2.2/3.0 | 8.1 | Circular saw | ■ | ■ | ■ | ■ | ■ |
| FS 550 (Saw) | 56.5 | 2.8/3.8 | 10.0 | Kreissägeblatt | ■ | ■ | ■ | - | ■ |
| FS 550 (Mow) | 56.5 | 2.8/3.8 | 10.0 | Circular saw or Brush knife | ■ | ■ | ■ | - | ■ |

□ Retrofittable ■ Standard

¹⁾ Without cutting tool and deflector

The versions available in each country may differ from the above range and specifications; subject to change without notice. Please consult your STIHL dealer.