

Model	Displacement cm <sup>3</sup>	Power output kW/bhp	Weight kg <sup>1)</sup>	Cutting tool	Elasto- Start	Anti-vibration system	4-MIX engine	Double handle
FS 85	25.4	0.95/1.3	5.3	Metal blade 230-2	■	■	-	■
FS 85 R	25.4	0.95/1.3	5.0	Metal blade 230-2	■	■	-	-
FS 87	28.4	0.95/1.3	5.6	Metal blade 230-2	-	■	■	■
FS 90	28.4	0.95/1.3	5.8	Metal blade 230-2	-	■	■	■
FS 100	31.4	1.05/1.4	5.8	Metal blade 230-2	-	■	■	■
FS 120	30.8	1.3/1.8	6.3	Metal blade 230-2	■	■	-	■
FS 130	36.3	1.4/1.9	5.9	Metal blade 230-2	-	■	■	■
FS 200	36.3	1.6/2.2	6.3	Metal blade 230-2	■	■	-	■
FS 250	40.2	1.6/2.2	6.3	Metal blade 230-4	■	■	-	■

□Retrofittable ■Standard

<sup>1)</sup>Without cutting tool and deflector

The versions available in each country may differ from the above range and specifications; subject to change without notice. Please consult your STIHL dealer.