

Model	Displacement cm ³	Power output kW/bph	Weight kg ¹⁾	Bar length cm	Elasto- Start	Antivibration system	Rotating multi-function handle	Tool free filler cap
HS 45, 45 cm	27.2	0.75/1.0	4.7	45	■	■	-	-
HS 45, 60 cm	27.2	0.75/1.0	5.0	60	■	■	-	-
HS 81 R, 60 cm	22.7	0.7/1.0	5.5	60	-	■	■	■
HS 81 R C-E	22.7	0.7/1.0	5.6	60	-	■	■	■
HS 81 R, 75 cm	22.7	0.7/1.0	5.7	75	-	■	■	■
HS 81 T, 50 cm	22.7	0.7/1.0	5.0	50	-	■	■	■
HS 81 T, 60 cm	22.7	0.7/1.0	5.2	60	-	■	■	■
HS 81 T, 75 cm	22.7	0.7/1.0	5.4	75	-	■	■	■
HS 81 T C-E	22.7	0.7/1.0	5.3	60	-	■	■	■
HS 86 R	22.7	0.7/1.0	5.5	75	-	■	-	■
HS 86 T, 75 cm	22.7	0.7/1.0	5.2	75	-	■	-	■

□Retrofittable ■Standard

¹⁾With cutter

The versions available in each country may differ from the above range and specifications; subject to change without notice. Please consult your STIHL dealer.