

Model	Power output kW	Weight kg	Working pressure bar	Max. water throughput l/h	Rotary nozzle	Integrated hose drum	Pressure gauge and pressure / flow control	2 spray lance holders	Aluminium telescopic handle
RE 108	1.7	15.0	10-110	440	■	-	-	-	■
RE 118	2.1	17.0	10-125	500	■	-	-	-	■
RE 128 PLUS	2.3	17.0	10-135	500	■	■	-	-	■
RE 142	2.9	23.0	10-140	610	■	-	■	-	-
RE 142 PLUS	2.9	23.5	10-140	610	■	■	■	-	-
RE 162 PLUS	3.3	24.5	10-150	650	■	■	■	-	-
RE 271 PLUS	3.2	40.0	20-140	660	■	■	■	■	-
RE 281 PLUS	4.2	40.0	20-160	760	■	■	■	■	-
RE 361	6.5	60.0	20-180	1080	□	-	■	-	-
RE 361 PLUS	6.5	73.0	20-180	1080	■	■	■	-	-
RE 461 PLUS	7.8	89.0	20-220	1130	■	■	■	-	-
RE 471 PLUS	7.8	89.0	20-180	1300	■	■	■	-	-

□Retrofittable ■Standard

The versions available in each country may differ from the above range and specifications; subject to change without notice. Please consult your STIHL dealer.